

# CENTRA

## TECHNICAL DATA

CERTIFICATION & CLASSIFICATION	STANDARDS	CENTRA
Type of floor covering	ISO 10581	Homogeneous single layered vinyl flooring
Classification	ISO 10874	Commercial: 34 Industrial: 43
Wear layer binder content	ISO 10581	Type I.

### TECHNICAL CHARACTERISTICS

Total thickness	ISO 24346	2.0 mm
Total weight	ISO 23997	3000 g/m <sup>2</sup>
Wear layer thickness	ISO 24340	2.0 mm
Surface treatment		PUR reinforced
Form of delivery	ISO 24341 Sheet (rolls)	Approx. 23 running metres x 200 cm Art. no. 21086 __ _ 3 digit colour number

### PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)

Declaration of Performance	EN 14041	019-0058-DoP-2018-05
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bi-s1 ≥ 8 kW/m <sup>2</sup> Pass
Thermal resistance	EN 12667	Approx. 0.01 m <sup>2</sup> K/W
Slip resistance	EN 13896	≥ 0.3

### TECHNICAL PERFORMANCES

Residual indentation	ISO 24343-1	Required value: ≤ 0.10 mm Best measured value: 0.03 mm
Slip resistance	DIN 51130	R9
Bacteria resistance	ISO 846:Part C	Does not favour growth
Chemical resistance	ISO 26987	Good resistance
Castor chair	ISO 4918	Suitable
Flexibility	ISO 24344	Pass
Dimensional stability	ISO 23999	≤ 0.40 %
Light fastness	EN ISO 105-B02	≥ 6
Seam strength	EN 684	Average value: ≥ 240 N/50 mm Individual values: ≥ 180 N/50 mm
Static electrical discharge	EN 1815	< 2 kV
Underfloor heating		Suitable - max. 27°C

### ENVIRONMENTAL PERFORMANCES

Total VOC emissions	ISO 16000-6	≤ 10 µg/m <sup>3</sup> (after 28 days)
---------------------	-------------	--

### COLOURS

18

The above information is subject to modification for the benefit of further improvement. (04/18)

According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website [www.tarkett.com](http://www.tarkett.com)

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

Colours of the products shown in the photos or samples are indicative only. There may be differences in colours, gloss and embossing structure between the products sold and photos or samples.