

Specjal S

TECHNICAL DATA	STANDARD	SPECJAL S
CLASSIFICATION		
Classification	EN ISO 10581	Homogeneous single layered vinyl flooring
	EN ISO 10874	Commercial: 34 / Industrial: 43
CE certification	EN 14041	Yes
Wear layer binder content	EN ISO 10581	Type II
TECHNICAL CHARACTERISTICS		
Total thickness	EN ISO 24346	2.0 mm
Total weight	EN ISO 23997	3700 g/m ²
Wear layer thickness	EN ISO 24340	2.0 mm
Surface treatment		PU
Form of delivery	EN ISO 24341 Sheet (rolls)	20 running metres x 200 cm Art. no. 21099 _ _ _ 3 digit colour number
	EN ISO 24342 Tiles (box)	61 x 61 cm - 16 tiles/box = 5.95 m ² Art. no. 21100 _ _ _ 3 digit colour number
PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)		
Declaration of Performance	EN 14041	0019-0063-DoP-2019-05
Reaction to fire	EN ISO 13501-1 EN ISO 9239-1 EN ISO 11925-2	Bfl-s1 ≥ 8 kW/m ² Pass
Static electrical discharge	EN 1815	< 2.0 kV
Thermal resistance	EN 12667	Approx. 0.01 m ² K/W
Slip resistance	EN 13893	μ ≥ 0,3
TECHNICAL PERFORMANCES		
Residual indentation	EN ISO 24343-1	Required value: ≤ 0.10 mm Best measured value*: 0.04 mm
Slip resistance	DIN 51130	R9
Castor chair	ISO 4918	Suitable
Light fastness	EN ISO 105-B02	≥ level 6
Dimensional stability	EN ISO 23999	≤ 0.40% for rolls ≤ 0.25% for tiles
Flexibility	ISO 24344	Pass
Bacteria resistance	ISO 846 Part C	Does not favour growth
Underfloor heating		Suitable - max. 27°C
Seam strength	EN 684	Average value: ≥ 240 N/50mm Individual values: ≥ 180 N/50mm
ENVIRONMENTAL PERFORMANCES		
Total VOC emissions	ISO 16000-9	≤ 10 μg/m ³ (after 28 days)
COLOURS		
		10

The above information is subject to modification for the benefit of further improvement. (06/19). *For information - not binding.
 According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com
 Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



Colour No.	Welding No.	Colour No.	Welding No.	Colour No.	Welding No.	Colour No.	Welding No.	Colour No.	Welding No.
21099 343	1294 680	21099 345	1287 254	21099 373	1291 352	21099 376	1287 046	21099 378	1287 802
21099 344	1294 727	21099 371	1291 215	21099 374	1287 800	21099 377	1287 777	21099 380	1287 804

For informations, please contact:

sales-wa@polystyl-asia.com
 (India, Sri Lanka, Maldives, Bangladesh, Bhutan, Nepal, Pakistan)

sales-sea@polystyl-asia.com
 (Singapore, Vietnam, Cambodia, Thailand, Malaysia, Philippines, Indonesia, Myanmar, Brunei)

sales-nea@polystyl-asia.com
 (Japan, South-Korea, Taiwan, Hong Kong, Macau)

Specjal S

HOMOGENEOUS COMPACT VINYL

The Fresh
basics of
Homogeneous
solutions

Specjal S

phthalate free
100%



ROLL

TILE

Printed on 100% recycled paper and cardboard - ♻️ recyclable

Customs tariff: 4820500000

Specjal S - 310001 0011 - 06/19

Specjal S

- Warm and cold neutrals
- Easy to combine
- Available in sheets and tiles
- Factory applied base for future maintenance procedures



LRV: 55%

cool grey

© 21099 343 NCS S 2002-B
□ 21100 343

LRV: 38%

blue

© 21099 380 NCS S 3030-R90B
□ 21100 380

LRV = Luminous Reflectance Value

LRV: 45%

warm grey

© 21099 371 NCS S 3000-N
□ 21100 371



LRV: 33%

grey

© 21099 345 NCS S 4000-N
□ 21100 345

LRV: 16%

dark grey

© 21099 344 NCS S 6005-N
□ 21100 344

LRV: 56%

yellow beige

© 21099 376 NCS S 2010-Y30R
□ 21100 376

LRV: 54%

light beige

© 21099 373 NCS S 2005-Y60R
□ 21100 373

LRV: 41%

beige

© 21099 374 NCS S 3010-Y50R
□ 21100 374

LRV: 35%

dark yellow

© 21099 377 NCS S 3030-Y20R
□ 21100 377

LRV: 40%

green

© 21099 378 NCS S 3010-G10Y
□ 21100 378

